

# Antique coating

## General Information

---

Article number:	<b>AF1-300</b>
Usage:	Technically improved glue-based distemper for interior work with high covering power, reversible. Outstanding processing properties, high spreading rate. Very high vapour and CO <sub>2</sub> diffusion properties, practically free of tension.
Characteristics:	Reversible, low-tension, free of VOC, solvents and softening agents, biologically degradable.
VOC:	EU limit value of the product (cat. A/a): 30 g/l (2010). This product contains max. 3 g/l VOC.
Basis:	Glue-based distemper, delayed solubility.

## Physical properties

---

Colour:	antique white (other colour shades available on request)
Gloss level:	flat mat
Density:	1.5 g/ml
Consumption:	According to the surface 0.1 - 0.3 l/m <sup>2</sup> for one coat of paint.
Covering rate:	1 litre covers 3.5 to 10 m <sup>2</sup> (one coat of paint).
Tinting:	only possible on site

## Application

---

Application:	Please pay attention to a uniform layer that is free of gaps. Only use clean working equipment.
Substrates:	Any sustainable, mineral surface. The surfaces must be sustainable and stable, clean, dry and free from dirt, oil and grease and other separating substances. Existing coatings should be tested for sustainability and coats with unsuitable adhesion must be removed completely.
Recommended Treatment:	Strongly absorbing or sanding surfaces must be pre-treated with griwecolor Deep Sealer. Surfaces with mould growth and substrates with stains from nicotine, water, soot or grease should be pre-treated separately.
Thinning:	Not necessary, product is ready to use. If necessary, it can be diluted with water.
Processing equipment:	Brush or roller.

## Antique coating

Processing temperature:	minimum +5 °C air and object temperature
Drying:	Repainting possible after approx. 4 - 6 hours, depending on temperature and air humidity. In case of lower temperatures and higher air humidity drying times are extended. Please ensure adequate ventilation.
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

### Consignment & Storage

---

Packaging:	Trading units with 15 l content.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. Keep out of reach of children.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

### Hazardous warning

---

No labelling required as product is non-hazardous.  
Please also follow the instructions on the MSDS.

**If you need assistance, we will be pleased to be at your service at any time.  
Please contact us.**

Our technical data sheets and brochures are to inform you to the best of the company's knowledge.  
However, they are not legally binding.