

Profi

General Information

Article number:	PR1-500
Usage:	Filling latex one-coat-paint with high covering power for high-class interior work.
Characteristics:	High filling power, outstanding processing properties. DIN 53778: scrub resistant, mat Covering power class 2 for consumption 7 m ² /l.
Wet abrasion class:	Wet abrasion class 2 according to DIN EN 13300.
VOC:	EU limit value of the product (cat. A/a): 30 g/l (2010). This product contains max. 30 g/l VOC.
Basis:	Titanium dioxide, natural fillers, terpolymere synthetic resin dispersion.

Physical properties

Colour:	white / antique white (other colour shades available on request)
Gloss level:	mat
Density:	1.64 g/ml
Consumption:	According to the surface 0.1 - 0.3 l/m ² for one coat of paint.
Covering rate:	1 litre covers 4 to 10 m ² (one coat of paint).
Tinting:	With griwecolor Full shade tinting paints (max. 5 %).

Application

Application:	Please pay attention to a uniform layer that is free of gaps. Only use clean working equipment. You will reach the processing viscosity after stirring vigorously / electrically.
Substrates:	Woodchip paper (first coat) and many other surfaces. The substrate must be dry, clean, sustainable and stable. Existing coatings with unsuitable adhesion must be removed completely.
Recommended treatment:	Strongly absorbing or sanding surfaces must be pre-treated with griwecolor Deep Sealer. Surfaces with mould growth and substrates with stains from nicotine, water, soot or grease should be pre-treated separately.
Thinning:	1% - 3% with water.
Processing equipment:	Brush, roller or suitable spraying machines.

Profi

Processing temperature:	minimum +5 °C air and object temperature
Drying:	Repainting possible after approx. 4 - 6 hours, depending on temperature and air humidity. In case of lower temperatures and higher air humidity drying times are extended.
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

Consignment & Storage

Packaging:	Trading units with 5 l, 10 l or 15 l content.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. Keep out of reach of children.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

Hazardous warning

No labelling required as product is non-hazardous.
Please also follow the instructions on the MSDS.

**If you need assistance, we will be pleased to be at your service at any time.
Please contact us.**

Our technical data sheets and brochures are to inform you to the best of the company's knowledge.
However, they are not legally binding.