

Article No.: SL1-600 griwecolor Satin latex
Print date: 03.08.2022 Revision date: 03.08.2022
Version: 4.2 Issue date: 03.08.2022

EN
Page 1 / 7

griwecolor Satin latex

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): SL1-600
Trade name/designation griwecolor Satin latex
white

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

see as in techn. data sheet

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

griwecolor GmbH
Wieselbrunnen 2 Telephone: +49(0)7707 9904-0
D-78199 Bräunlingen-Döggingen

Department responsible for information:

Herr Grieshaber
E-mail (competent person) info@griwecolor.de

1.4. Emergency telephone number

Emergency telephone number +49 (0)7707 99040
Only available during office hours.
8.00 - 12.00 / 13.00 - 16.30

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1); 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description: waterbased Dispersion

Hazardous ingredients:

Article No.: SL1-600
Print date: 03.08.2022
Version: 4.2

griwecolor Satin latex
Revision date: 03.08.2022
Issue date: 03.08.2022

EN
Page 2 / 7

griwecolor Satin latex

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
236-675-5		
13463-67-7	Titanium dioxide	12,5 - 25
022-006-00-2	Carc. 2 H351	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

The product itself does not burn.

Suitable extinguishing media

Not applicable

Unsuitable extinguishing media

Not applicable

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon monoxide, carbon dioxide, smoke, nitrogen oxides.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.

Additional information

Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing

Article No.: SL1-600 griwecolor Satin latex
Print date: 03.08.2022 Revision date: 03.08.2022
Version: 4.2 Issue date: 03.08.2022

EN
Page 3 / 7

griwecolor Satin latex

agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Not applicable.

Further information on storage conditions

Store in a well-ventilated and dry room at temperatures between 5 °C and 25 °C. Protect from sunlight. Take care of instructions on label.

Protect against: Frost

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Personal protection equipment

Respiratory protection

Not applicable.

Hand protection

For prolonged or repeated handling the following glove material must be used: PVC (polyvinyl chloride)

Thickness of the glove material > 0,4 mm; Breakthrough time: >480 min .

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin: . Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes. Recommended eye protection articles: Wear eye glasses with side protection according to EN 166.

Body protection

Wear dust-resistant protective clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Article No.: SL1-600
Print date: 03.08.2022
Version: 4.2

griwecolor Satin latex
Revision date: 03.08.2022
Issue date: 03.08.2022

EN
Page 4 / 7

griwecolor Satin latex

Colour:	refer to label
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	100 °C Source: water
Flammability:	not applicable
Lower and upper explosion limit:	
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable
Flash point:	not applicable
Auto-ignition temperature:	not applicable
Decomposition temperature:	not applicable

pH at 20 °C:	7 - 8,8 / 100,0 weight-%
Viscosity at 20 °C:	thixotropic
Solubility(ies):	
Water solubility at 20 °C:	miscible
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	not applicable
Density and/or relative density:	
Density at 20 °C:	1,45 g/cm ³
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. Other information

solvent content:	
Organic solvents:	0,1 weight-%

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

Not applicable.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

griwecolor Satin latex

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

griwecolor Satin latex

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

- 14.1. **UN number or ID number** not applicable
- 14.2. **UN proper shipping name** not applicable
- 14.3. **Transport hazard class(es)** not applicable
- 14.4. **Packing group** not applicable
- 14.5. **Environmental hazards**
Land transport (ADR/RID) not applicable
Marine pollutant not applicable
- 14.6. **Special precautions for user**
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**
Tunnel restriction code -
- Sea transport (IMDG)**
EmS-No. not applicable
- 14.7. **Maritime transport in bulk according to IMO instruments**
No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
- Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**
VOC-value (in g/L): 2,8
- Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**
VOC product category: (Cat. A/a) ; VOC limit value: 30 g/l
Maximum VOC content of the product in a ready to use condition (in g/L): 2,8
- National regulations**
- Restrictions of occupation**
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
- 15.2. **Chemical Safety Assessment**
Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

*

griwecolor Satin latex

Full text of classification in section 3:

Carc. 2 / H351 Carcinogenicity Suspected of causing cancer if inhaled.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EmS-No.	Emergency Response Procedures for Ships Carrying Dangerous Goods
EN	European Standard
EU	European Union
EEC	European Economic Community
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Data sources

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version