

## Technical Data Sheet

Last revision: 10.12.2021

# Quartz Primer

### General Information

---

Article number:	<b>QG1-600</b>
Usage:	Quartz-containing primer with excellent adhesion to many substrates. Suited for all types of plaster with smooth or weakly absorbing substrates.
Weather-resistance:	Weather resistant according to DIN EN 18363 - 3.1.10.3.
VOC:	EU limit value of the product (cat. A/h): 30 g/l (2010). This product contains max. 14 g/l VOC.
Basis:	Acrylic copolymer dispersion, titanium dioxide, quartz sand and natural fillers.

### Physical properties

---

Colour:	antique white
Gloss level:	mat
Density:	approx. 1.6 g/ml
Consumption:	Number of coats: 1 On smooth surfaces 200 - 300 g/m <sup>2</sup> for one coat of paint. On rough surfaces 400 - 600 g/m <sup>2</sup> for one coat of paint.
Covering rate:	1 litre covers approx. 3 - 5 m <sup>2</sup> (smooth surface) respectively approx. 2 m <sup>2</sup> (rough surface) per coat of paint.

### Application

---

Application:	Please stir up before use. Please pay attention to a uniform layer that is free of gaps. Only use clean working equipment.
Substrates:	Plasters, concrete, non-ferrous metal, PVC. The surfaces must be sustainable, clean, dry and free from dirt, oil and grease and other separating substances. Existing coatings should be tested for sustainability and coats with unsuitable adhesion must be removed completely.
Thinning:	Not necessary. If required add maximal 5 % of water.
Processing equipment:	Brush or roller.
Processing temperature:	Minimum +5 °C air and object temperature.
Drying:	Can be worked over after 12 hours drying time. Please ensure adequate ventilation.
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

---

## Technical Data Sheet

Last revision: 10.12.2021

# Quartz Primer

### Consignment & Storage

---

Packaging:	Trading units with 8 kg or 25 kg content.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. Keep out of reach of children.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

### Hazardous warning

---

No labelling required as product is non-hazardous.  
Please also follow the instructions on the MSDS.

### You want advice?

Get in touch with us. We are looking forward to your inquiry.