

Technical Data Sheet

Last revision: 10.12.2021

Strippable coatings

General Information

| | |
|------------------|--|
| Article number: | spreadable: AZ0-700 (colourless), AZ1-700 (white) Airless: AZ0-701 (colourless), AZ1-701 (white) |
| Usage: | griwecolor Strippable coating is based on an aqueous dispersion and has excellent film characteristics. It is used to protect spraying booths, conveyor belts, hangers and hooks, walls and gratings. It is also suited as a temporary transport protection for high-class components. |
| Characteristics: | Solvent free, odourless, quickly drying. |
| Basis: | Aqueous vinylacetate-synthetic dispersion. |

Physical properties

| | |
|--------------|--|
| Colour: | colourless / white |
| Viscosity: | working consistency |
| Density: | 1,065 g/ml |
| Consumption: | depending on the surface approx. 300 ml/m ² |

Application

| | |
|-------------------------|--|
| Application: | Please pay attention to a uniform layer that is free of gaps. The minimum layer thickness is 80-100 µm. The soiled coating can be pulled off dry (cutting with a sharp object facilitates the removal of the coating) |
| Substrates: | Smooth substrate for example zinc sheet, aluminium, glass etc. In order not to compromise the tearability of the dry coating, please pay attention to a clear surface which is free from dirt. Be careful: We principally advise a tearability test beforehand when using coated surfaces and synthetic surfaces! |
| Thinning: | Not necessary, product is ready to use. If necessary, it can be diluted with water. |
| Processing equipment: | Brush, roller or suitable spraying equipment. |
| Processing temperature: | minimum +5 °C object resp. substrate temperature. |
| Drying: | Let it air-dry overnight. Ensure sufficient ventilation. |
| Clean-Up: | Immediately in the wet state with water, if necessary in addition with a household detergent. |

Technical Data Sheet

Last revision: 10.12.2021

Strippable coatings

Consignment & Storage

| | |
|------------|---|
| Packaging: | Trading units with 6 kg, 16 kg or 30 kg capacity. |
| Storage: | Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. |
| Disposal: | Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS. |

Hazardous warning

No labelling required as product is non-hazardous.
Please also follow the instructions on the MSDS.

You want advice?

Get in touch with us. We are looking forward to your inquiry.