

Strippable coatings

General Information

Article number:	spreadable: AZ0-700 (colourless), AZ1-700 (white) Airless: AZ0-701 (colourless), AZ1-701 (white)
Usage:	griwecolor Strippable coating is based on an aqueous dispersion and has excellent film characteristics. It is used to protect spraying booths, conveyor belts, hangers and hooks, walls and gratings. It is also suited as a temporary transport protection for high-class components.
Characteristics:	Solvent free, odourless, quickly drying.
Basis:	Aqueous vinylacetate-synthetic dispersion.

Physical properties

Colour:	colourless / white
Viscosity:	working consistency
Density:	1,065 g/ml
Consumption:	depending on the surface approx. 300 ml/m ²

Application

Application:	Please pay attention to a uniform layer that is free of gaps. The minimum layer thickness is 80-100 µm. The soiled coating can be pulled off dry (cutting with a sharp object facilitates the removal of the coating)
Substrates:	Smooth substrate for example zinc sheet, aluminium, glass etc. In order not to compromise the tearability of the dry coating, please pay attention to a clear surface which is free from dirt. Be careful: We principally advise a tearability test beforehand when using coated surfaces and synthetic surfaces!
Thinning:	Not necessary, product is ready to use. If necessary, it can be diluted with water.
Processing equipment:	Brush, roller or suitable spraying equipment.
Processing temperature:	minimum +5 °C object resp. substrate temperature.
Drying:	Let it air-dry overnight. Ensure sufficient ventilation.
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

Strippable coatings

Consignment & Storage

Packaging:	Trading units with 6 kg, 16 kg or 30 kg capacity.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

Hazardous warning

No labelling required as product is non-hazardous.
Please also follow the instructions on the MSDS.

Our technical data sheets and brochures are to inform you to the best of the company's knowledge.
However, they are not legally binding.